



PINE RED LION 16" WIDTHS AND OFFSETS

Width	5" inner		5.5" inner		6" inner		6.5" inner		7" inner		7.5" inner	
	Lip width	Offset	Lip width	Offset	Lip width	Offset	Lip width	Offset	Lip width	Offset	Lip width	Offset
7.0J	2"	-13										
7.5J	2.5"	-19	2"	-6								
8.0J	3"	-25	2.5"	-13	2"	0						
8.5J	3.5"	-32	3"	-19	2.5"	-6	2"	+6				
9.0J	4"	-38	3.5"	-25	3"	-13	2.5"	0	2"	+13		
9.5J	4.5"	-44	4"	-32	3.5"	-19	3"	-6	2.5"	+6	2"	+19
10.0J	5"	-51	4.5"	-38	4"	-25	3.5"	-13	3"	0	2.5"	+13
10.5J	5.5"	-57	5"	-44	4.5"	-32	4"	-19	3.5"	-6	3"	+6
11.0J	6"	-64	5.5"	-51	5"	-38	4.5"	-25	4"	-13	3.5"	0
11.5J	6.5"	-70	6"	-57	5.5"	-44	5"	-32	4.5"	-19	4"	-6
12.0J	7"	-76	6.5"	-64	6"	-51	5.5"	-38	5"	-25	4.5"	-13
12.5J	7.5"	-83	7"	-70	6.5"	-57	6"	-44	5.5"	-32	5"	-19
13.0J	8"	-89	7.5"	-76	7"	-64	6.5"	-51	6"	-38	5.5"	-25
13.5J	8.5"	-95	8"	-83	7.5"	-70	7"	-57	6.5"	-44	6"	-32
14.0J			8.5"	-89	8"	-76	7.5"	-64	7"	-51	6.5"	-38
14.5J					8.5"	-83	8"	-70	7.5"	-57	7"	-44
15.0J							8.5"	-76	8"	-64	7.5"	-51

PCD	C. BORE
5X100	65.0
5X108	70.0
5X110	70.0
5X112	70.0
5X114.3	70.0
5X120	70.0

FACE COLOURS
METALLIC MOSS
DEEP BLACK
BRIGHT RED
GOLD PEARL

Three piece construction
Made in New Zealand
Uncoated polished lips - require regular buffing to maintain an optimal shine
Pine wheels are not approved to JWL/VIA/TÜV road standards

www.pine-engineering.co.nz

PINE ENGINEERING LIMITED NZ